



# LES PLÉIADES 10W-50

**Fully synthetic and very high performance lubricant based on ELF technology.  
Special made for SUBARU Boxer Engines, approved as SUBARU Genuine oil**

## APPLICATIONS

Suitable for SUBARU boxer engines

Adapt in the severe conditions

Fit for high boost turbocharged engines

- Can be used for EJ and EZ type SUBARU boxer engines including turbocharged
- Perfectly adapt sport and race track type driving under the most difficult operating conditions
- Appropriate for IMPREZA WRX and other high output performance tuned boxer engines with the most stringent requirements

## PERFORMANCES

International specifications

API: SM/CF

Genuine approval

**SUBARU : Applicable engine types EJ15, EJ20, EJ25, EG33, EZ30 and EZ36 (both naturally aspirated and turbocharged boxer engines)  
\*Not applicable for FA and FB engines.**

## CUSTOMER BENEFITS

Anti-wear protection

- Maintains the most resistant oil films even at very high temperature
- Provides an exceptional anti-wear protection for the engine, especially in the most severe conditions

Thermal stability

- Outstanding thermal stability and oxidation resistance preventing degradation in the most severe conditions

Engine cleanliness

- Keeps the engine clean and develops performance and power

Extended engine life

- Lubricates engine parts immediately during cold starts, resulting in extended engine life

## CHARACTERISTICS

ELF LES PLÉIADES 10W-50	Method	Units	SAE Grade 10W-50
Viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	119.4
Viscosity at 100°C	ASTM 445	mm <sup>2</sup> /s	17.50
Viscosity Index	ASTM D2270	-	162
Viscosity HTHS 150°C	CEC L 36 A-90	mPa.s	4.5
Pour Point	JIS K2269	°C	-33.0
Flash Point	ASTM D92	°C	230
B.N.	ASTM D2896	mgKOH/g	10.6

The typical characteristics mentioned represent mean values

TOTAL LUBRIFIANTS  
562 avenue du parc de l'île  
92029 Nanterre  
1/1

Elf LES PLÉIADES 10W-50  
Sheet updated: 04/2012



This lubricant used in accordance with our recommendations and for the application for which it is intended does not represent a special hazard.  
A safety data file conforming to the requirements of current EC legislation is available from your local trade consultant.